

UT256 SERIES

200A TRUE RMS FORK METER



Intertek

UT256 series are high reliable, true RMS fork meters. Its unique design allows users to measure current by simply moving the wire of interest inside the opening of the 'fork' past the labeled mark. With no mechanical parts, this meter bears no risk from any type of mechanical failure.

	Range	UT256A	UT256B
AC current (A)	200A	±(1.8%+2)	±(2.5%+5)
DC current (A)	200A		±(2.5%+5)
AC voltage (V)	750V		±(1.2%+3)
	1000V	±(1.2%+3)	
DC voltage (V)	1000V	±(0.8%+3)	±(0.8%+3)
Resistance (Ω)	60MΩ	±(1%+2)	±(1%+2)
Capacitance (F)	60mF		±(4%+20)
Frequency (Hz)	10~10kHz	±(0.1%+5)	
Features			
Display count		6000	6000
Auto range		√	√
True RMS		√	√
Diode test	About 3V		√
NCV		Tricolor	√
Data hold		√	√
Zero mode			√
Relative mode			√
LCD backlight		√	√
Auto power off	About 15 minutes	√	√
Continuity buzzer		√	√
Low battery indication	≤2.4V	√	√
Input protection		√	√
Input impedance	≥10MΩ	√	√
Power	1.5V battery (LR6) x 2		
Display	UT256A: 35mm x 26mm; UT256B: 36.5mm x 24mm		
Product color	Red and grey		
Product net weight	UT256A: 251g; UT256B: 163.7g		
Product size	UT256A: 217mm x 58.8mm x 38.5mm; UT256B: 210mm x 53mm x 35mm		
Standard accessories	Batteries, test leads		
Standard individual packing	Gift box, carrying bag, English manual		
Standard quantity per carton	20pcs		
Standard carton measurement	485mm x 310mm x 205mm		
Standard carton gross weight	9.5kg		



● UT256A



● UT256B

