

REVISIONS			
REV #	DESCRIPTION	APPV.	REV DATE



This tool is used to tension the steel straps which are mounted on the poles to hold the bracket in place.

*** Features**

- ▶ Drop forged banding tool.
- ▶ It has built-in cutter for stainless steel bands 3/8" ~ 3/4" width x 0.03" thickness max.
- ▶ All parts are heat-treated.
- ▶ Specially designed holding dog to work with tough and hard stainless steel banding in the market.
- ▶ Epoxy coating provides protection from corrosion and oxidation.

*** How to use this tensioner**


- 1) Slide the steel banding onto the buckle and pass it around the object.
- 2) Loop the steel strapping once more through the buckle for extra strength.
- 3) Install the stainless steel band into the opening of the tool nose and grip.
- 4) Turn the handle to apply tension to stainless steel banding.
- 5) Pull the handle to cut the banding.
- 6) Hammer down the tabs of the steel buckle to secure the strap in place.

NOTE :

- 1) MATERIAL : AS SPECIFIED
- 2) FINISH : AS SPECIFIED



AXIS ELECTRICAL COMPONENTS (I) P. LTD.
MUMBAI - 400067, INDIA.
TEL : 91-22-67756000,
e-mail:marketing@axis-india.com



MATERIAL :
REF NOTE

DRAWN:	NB
CHECKED:	AG
APPROVED:	SD
ISSUE DT:	31/08/2020
SCALE:	DO NOT SCALE.

DRG No: 4418-2020 C

TITLE :
TENSIONER STRAP
FIXING TOOL